

# SATIN FINISH

## PRODUCT DESCRIPTION

Satin Finish is an unique product designed to enhance the natural look and color of all flamed, sandblasted, spill face, tumbled and textured surfaces including limestone, granite, slate, marble, cast and natural stone. When used in conjunction with Star Impregnator or Triple Star Impregnator, Satin Finish seals and protects while leaving a beautiful low maintenance satin sheen. Satin Finish allows vapor transmission while offering a slip, resistant scuff resistant and water resistant surface. Satin Finish is U.V. transparent and non-yellowing. Satin Finish is equally effective in interior and exterior applications. Due to the difference of each material, several inconspicuous test patches should be completed to assure maximum performance. user must determine suitability of the product for intended use.

## APPLICATION INSTRUCTIONS

For best results, the surface should be clean, dry and free from frost and dust. Do not apply in extremely cold or hot conditions. Where extra stain protections is not necessary, Satin Finish can be used by itself. To protect against oils and grease, apply Star Impregnator or Triple Star Impregnator as directed. This procedure assures maximum stain prevention.

## NEW INSTALLATION BEFORE GROUTING

Apply Star Impregnator or Triple Star Impregnator on all surfaces prior to grouting. This step will allow quick and easy cleanup after grouting. Grout can stain many materials if the procedure is not used prior to grouting. Apply Star Impregnator or Triple Star Impregnator using a clean cotton towel, lambs wool applicator, rayon mop and pneumatic sprayer. Apply enough to wet surface. Be careful not to saturate the open grout joints. Allow Star Impregnator or Triple Star Impregnator to stand for 3 to 5 minutes for maximum penetration. All excess must be removed at this time with a clean dry towel. Allow Star Impregnator or Triple Star Impregnator to cure 24 hours before continuing with the grouting procedure.

## NEW INSTALLATION AFTER GROUTING

All access grout residue/haze must be removed with the appropriate cleaner before continuing. Apply Star Impregnator or Triple Star Impregnator to the grout joints using a point brush or towel. This procedure will protect the grout joint as well as the surface. Allow treated grout joint to cure for 1 to 2 hours. Once cured, apply Satin Finish to the entire surface using a clean white towel, natural fiber brush or pump sprayer. If a pump sprayer is used, it should be evened out with a brush before it dries on the surface. Do small areas or 30 to 60 square feet (3 to 8 meters) at a time. Do not allow Satin Finish to puddle on the surface. Two or more applications can be applied. Proceed with the subsequent applications after the previous application has dried to the touch (approximately 1 to 2 hours). Be sure to even out Satin Finish on the surface, blending in overlaid marks.

## EXISTING INSTALLATION

Remove any existing wax, coating or other sealers with Starship or appropriate stripper. Clean the surface and grout with Starclean per the instructions. Apply Star Impregnator or Triple Star Impregnator and Satin Finish as previously directed.



## CURE TIME

Although Satin Finish requires a 24-hour curing time, it will dry to the touch in 1 to 2 hours and may be used for normal foot traffic. For optimum results, the area should be kept dry and free from staining materials for 72 hours.

## COVERAGE

Coverage will vary depending on the density, porosity, texture, surface absorption and application methods. Satin Finish will cover approximately 200 to 800 square feet per gallon (20 to 80 square meters per 3.785 liters).

## MAINTENANCE

Regular maintenance will consist of using Starclean as directed. Re-application of Satin Finish will depend on the amount of foot traffic, abuse and type of material. Satin Finish can easily be removed using Starstrip.

## STORAGE

Store Satin Finish in the original container, properly sealed to avoid contamination and solvent evaporation. Stored at 77 degrees Fahrenheit (40 degrees Centigrade). Satin Finish will have a shelf life of 12 months.

## WARNING

Satin Finish contains combustible petroleum distillates. All solvents must be considered toxic and must be used in well ventilated areas. Good ventilation means that fresh air is flowing in such way as to feel a slight breeze. Use open windows and fans to move air. Continue to ventilate until vapors are eliminated. Exposure to high vapor concentration must be avoided. Inhaling the vapors can be harmful. Keep away from heat and open flames. Avoid prolonged contact with skin. Gloves should be worn at all times. Keep small children and pets out of area until thoroughly dried.

## QUANTITIES AVAILABLE

**Case (12) 1 gal. Container  
(4), 1 gal. Containers**